

Licensed Vehicle CCTV

Technical Specification and System Requirements

In order to be considered suitable for installation in any licensed vehicle, a taxi camera system must meet the following requirements in the tables below:

1. Operational Technical Specifications

Ref	Specification	Details
1.1	100% solid state design or a proven vibration and shock resistant system	The system should not have any fan and the recording should be vibration and shock proof, i.e.: - Flash-based SSD (100% industrial grade), - Hard disk with both mechanical anti-vibration and anti-shock mechanism and self-recovery and self-check file writing system. SD cards will not be acceptable.
1.2	8 to 36 Volts DC	Operational between 8 and 36 volts DC.
1.3	Reverse polarity protected	System to be protected against reverse voltage.
1.4	Short circuit prevention	System to be protected against short circuits
1.5	Over voltage protection	System to be protected against high voltage transients likely to be encountered in the vehicle electrical system.
1.6	Automotive Electromagnetic Compatibility Requirements	The taxi camera equipment must be e-marked or CE-marked with confirmation by the equipment manufacturer as being non-immunity related and suitable for use in motor vehicles.

Ref	Specification	Details
1.7	“on/off switch	The device must be active at all times when the vehicle is in use as a private hire or hackney carriage vehicle. The switch that deactivates the system must be located within the vehicles boot or engine compartment (i.e. it must only be possible to deactivate the system from outside of the vehicle).
1.8	First-in/first-out buffer recording principle	The system must automatically overwrite to create a constant cycle recording.
1.9	Access record	A service log must be kept and maintained by the approved installer and the local authority.
1.10	Security, duration and auto-clearing of log files	Data must be available for 28 days from the date of capture.
1.11	Image recording formats and media	Images must be encrypted to a minimum of FIPS 140/2.
1.12	Image protection during power disruption	Images must be preserved in the event of loss of power. Battery back-up will not be permitted.
1.13	Unit must continue to operate after the ignition is switched off.	The Unit must have the ability to operate for at least 30 minutes without power from the ignition. The device must be hard wired to both constant and ignition supply.
1.14	Image and audio data shall be recorded and stored in a unit separate from the camera head	Self-contained storage cards within the camera head will not be acceptable.

Ref	Specification	Details
1.15	GPS capability	System must have GPS capability.
1.16	The system must be capable of recording audio time, synchronized to the recorded images.	If activated, the audio must record within the video file.
1.17	The system shall not record audio except when audio recording is activated by means of an approved trigger / panic switch	The system should have the ability to start recording audio data by means of a trigger switch.
1.18	The audio playback, when triggered, shall be in 'real time' and synchronised with the images that are captured.	All audio files must simply be added to the video files as a voiceover, not in separate files
1.19	Audio data and image data must be stored together, not in separate files, and must be protected against unauthorised access or tampering.	
1.20	The system must support testing of the audio function for installation set-up and inspection purposes.	
1.21	Recorded images by the system shall not be displayed within the vehicle.	The monitor may only display live images as clearly visible by having a glance around as per ICO specifications, it must not display recorded images

Ref	Specification	Details
1.22	The system must have a panic switch for audio activation	At least one trigger/audio activate button must be capable of being operated by the driver. Once activated, this switch must trigger the recording of video and audio in accordance with section 6.1 below.
1.23	The system must include a visual indicator that will clearly show when audio recording is taking place. This indicator must be visible to all passengers within the vehicle.	This may take the form of an indicator LED built into the audio activation switch which can clearly be seen by passengers.

2. Storage Capacity Technical Specification

Ref	Specification	Details
2.1	Minimum of 28 days i.e. (28 x 24 hours) of recording capacity	The camera system must be capable of recording and storing a minimum of twenty eight days of images of HD1 (720/288) size or better.
2.2	Images must be clear in all lighting conditions	System to provide clear images in bright sunshine, shade, dark and total darkness. Also, when strong back light is present without the need for additional components.

3. Camera Head Technical Specification

Ref	Specification	Details
3.1	Camera installation non-obstructive	The camera and all system components shall be installed in a manner that does not interfere with the driver's vision or view of mirrors or otherwise normal operation of the vehicle.

Ref	Specification	Details
3.2	Protected camera disconnect	The camera head shall be designed to disconnect for ease of removal and replacement only by maintenance personnel.
3.3	Special tools for adjustment/removal	To prevent inappropriate interference only tools supplied to authorised fitters should be capable of carrying out adjustments or removal.
3.4	Field of view to capture all passengers in the vehicle	The lens or the position of the camera must be of a type that captures the driver and all passengers of the vehicle on the recorded image. The lens must be of a style not to create a “fishbowl” effect.
3.6	Compatible for use in vehicles with a partition (shield)	The camera system must be adaptable to provide clear images when a vehicle is equipped with a shield. This may be accomplished with the use of multiple camera heads.
3.7	Number of cameras	The unit shall be capable of supporting up to four (4) cameras. Four cameras may be required to provide adequate coverage in larger vehicles and/or certain purpose built vehicles or external images.

4. Storage Device Technical specification

Ref	Specification	Details
4.1	Impact and shock resistance	The recorder shall be impact resistant, sufficient to withstand a typical car accident, or striking with a large, heavy object such as a suitcase.

Ref	Specification	Details
4.2	Controller in concealed location	The storage unit shall be concealed from within the passenger compartment and effectively inaccessible except by authorised personnel. For example in the luggage area.
4.3	Download port provision	The recorder shall be equipped with a communication port within the hard drive housing for downloading by authorised officer.
4.5	Download port cable length (1 foot minimum)	Download port shall be at least one foot in length for ease of download.
4.6	Recorder to be securely affixed to the vehicle	
4.7	Log to register each user access	
4.8	Log to register camera system parameter modifications	
4.9	Log to register each image download session	
4.10	Log to register modification/manipulation of downloaded images	
4.11	Log to register exporting of downloaded images	
4.12	Log to register exporting of downloaded clips	
4.13	Log file protected against unauthorised access	
4.14	Time/date stamp	All stored images must be time and date stamped.

Ref	Specification	Details
4.15	Vehicle ID number stamp	All stored images must have vehicle identification (VIN & or number plate).
4.16	Controller non-modifiable ID code stamp	Each recorded image shall be automatically stamped with a unique and non-modifiable code that identifies the controller that was used to record the image.
4.17	Controller (Storage Recorder)	Manufacturer to supply the Council with a supply of specialised tools to allow for removal of the controller and download of data when required

5. Specifications for video and audio recording rate

Ref	Specification	Details
5.1	Video image recording on system activation (when audio is not activated).	The system shall record images at a minimum rate of twenty five (25) images per second.
5.2	Video image recording when audio is activated.	The system shall record images at the rate of twenty five images per second during periods when audio recording is activated (either due to time requirement, or through activation by the driver trigger switch or passenger audio button).
5.3	When activated, audio recording must be in real time and synchronised with the video recording.	When activated, audio recording must be in real time and synchronised with the video recording.
5.4	System to continue to record images (and audio when applicable) when engine is off.	System must continue to record images (and audio when applicable) for 30 minutes after engine / ignition or override switch is switched off.

Ref	Specification	Details

6. Specification for activation via driver or passenger trigger/ audio button

Ref	Specification	Details
6.1	The activation of a trigger button when activated by driver or passenger.	The system must be fitted with at least one trigger button that once activated will trigger synchronised audio and video recording.

7. Downloading Technical Specification

Ref	Specification	Details
7.1	Provision of necessary software, cables, security keys to the Council Licensing Team.	
7.2	Windows compatible.	Once downloaded and converted.
7.3	Downloaded images stored in non-volatile media	
7.4	Downloaded images stored in secure format	
7.5	Verifiable image authenticity	Each image shall be watermarked with vehicle ID, and time and date, and be tamperproof.

Ref	Specification	Details
7.1	Provision of necessary software, cables, security keys to the Council Licensing Team.	
7.6	Wireless Download Prohibited	All wireless hardware to be disabled.
7.8	Filter the specific images for events and times for the approximate time of the crime committed.	The playback software must list the files in date and time slot order for ease of location of required file.

8. Requirements in relation to System Information

Ref	Specification	Details
8.1	Provision of service log	The unit manufacturer shall have a service log. The manufacturer shall also provide detailed instructions for the drivers with each unit.
8.2	Serial number indication on service log	The unit will be marked with a serial number.
8.3	Installation date indication	A certificate of installation must be provided which will indicate the installation date.
8.4	Clarity of operating instructions	The system shall be provided with clear and concise operation instructions which are written or presented with due consideration to varying levels of literacy.
8.5	Installation by authorised agents	The unit shall only be installed by manufacturer's authorised agents.

Ref	Specification	Details
8.6	Provision of authorised agents list to the Council Licensing Team	The manufacturer or supplier shall provide a list of all authorised agents to the Council Licensing Team.
8.7	Documentation	The manufacturer must provide clear and concise operating instructions which are written or presented in layman's terms. (Details on how the system operates)
8.8	Image Protection	All captured images must be protected using encryption software that meets or exceeds the current FIPS 140-2 (level 2) standard or equivalent.

9. System requirements in relation to Vehicle Inspection Facility – Inspections

Ref	Specification	Details
9.1	Provision of system status/health indicator	The driver shall have an indicator showing when the system is operational and when there is a malfunction. This should include the images as shown to verify the status of each camera.
9.2	Mounting location of system status/health indicator to be seen	The indicators shall be mounted in such a way so as to allow for ease of view.
9.3	Design and or installation to be testable as part of the vehicle compliance test (or persons acting on behalf of the council – such as vehicle inspectors)	The system shall be designed and installed such that the system may be easily tested as part of vehicle compliance test as prescribed.

10. General System Requirements

Ref	Specification	Details
10.1	Vandal and tamper resistance	All component parts must be securely mounted, hard wired and small and discreet enough to remove the risk of tampering.
10.2	Provision of statement of compliance	In addition to a formal test of all aspects of this requirement specification, a statement of compliance shall be provided and signed by an officer of the company.
10.3	Reliability in operational and environmental conditions	The system shall provide reliable and full functionality in all operational and environmental conditions encountered in the operation of taxis.
10.4	Programmability of image timing parameters	It shall be possible to change timing and parameters without the requirement to change components.
10.5	Training and Technical Support and Equipment	Manufacturer must provide the Council Licensing Team and West Mercia Police with a Training and Technical support
10.6	Software and Hardware	Manufacturer to supply the Council Licensing Team and West Mercia Police with a supply of cables and software to be installed under the supervision of the council's authorised staff.
10.7	Agreement between the Camera Manufacturer and the Council	Agreement to allow the Council and West Mercia Police access to the relevant software from the supplier so that in the event the manufacturer goes out of business, council will be able to support the system.